

VS(B,K)



VS116B/230

Supply voltage:
AC 230 V
Output contact:
1x changeover/ SPDT 16 A.



VS116K

Supply voltage:
AC 230 V and AC/DC 24 V
Output contact:
1x changeover/ SPDT 16 A.



VS308K

Supply voltage:
AC 230 V and AC/DC 24 V
Output contacts:
3x changeover/ TPDT 8 A.



VS316/24

Supply voltage:
AC/DC 24 V
Output contacts:
3x changeover/TPDT
16 A, possibility to be
connected into 3-phase
circuit.



VS316/230

Supply voltage:
AC 230 V
Output contacts:
3x changeover/ TPDT
16 A, possibility to be
connected into 3-phase
circuit.

VS(U)



VS116U

Supply voltage:
AC/DC 12-240 V
Output contact:
1x changeover/SPDT 16 A.



VS308U

Supply voltage:
AC/DC 12-240 V
Output contacts:
3x changeover/ TPDT 8 A.

782L



782L

Power relays plug-in
Output contacts: 4 x
changeover contact/
SPDT 6 A.
Plug-in type.



ES-15/4N - socket


Max. voltage: 12 A
Weight: 59 g
Mounting to DIN rail
Intended for 4-contact relay.

750L



750L

Power relays plug-in
Output contacts:
3 x changeover contact /
SPDT 10 A.
Plug-in type.



ES-11- socket

Max. current: 10 A
Weight: 60 g
Mounting to DIN rail
Intended for 3-contact
relay.

Overview table

Type	Design	Coil voltage	Output contact	Other features			Designation	Page of catalogue
				LED signal light	RC unit	Parallel diode		
VS116B/230	MINI	AC 230 V/50-60 Hz	1x16 A changeover/ SPDT	●	x	x	VS116/B230 MINI, with installation into junction box or ceiling that allows control of lights, shades or awnings drives	36
VS116K	1M-DIN	AC 230 and AC/DC 24 V	1x16 A changeover/ SPDT	●	●	●	as a separation relay (4kV), direct switching of appliances up to 4000 VA (e.g. heaters), well visible signalization, noiseless	36
VS116U	1M-DIN	AC/DC 12..240 V	1x16 A changeover/ SPDT	●	●	●	as VS116K, but multivoltage supply coil	36
VS308K	1M-DIN	AC 230 and AC/DC 24 V	3x 8 A changeover/ TPDT	●	●	●	a "multiplication" of contacts, 3x changeover contact/ 3PDT only in 1-MODULE, well visible signalization, noiseless	36
VS308U	1M-DIN	AC/DC 12..240 V	3x 8 A changeover/ TPDT	●	●	●	as VS308K, but multivoltage supply coil	36
VS316/24	1M-DIN	AC/DC 24 V	3x16 A changeover/ TPDT	●	●	●	3x changeover contact in 1-MODULE, possibility of "multiplication" of contacts and in the same time possibility of switching high output, possibility of 3 phase switching	36
VS316/230	1M-DIN	AC 230 V	3x16 A changeover/ TPDT	●	●	●	as VS316/24, but AC 230 V	36
782L	PLUG-IN	AC 6-230 V, DC 6-110 V	4x6 A changeover/ 4PDT	●	x	x	compact small relay for installation into plug relay, basic version equipped by LED indication, detent and testing lever	38
750L	PLUG-IN	AC 6-230 V, DC 6-110 V	3x10 A changeover/ 3PDT	●	x	x	as 782L, but into 11-pin round socket, 3x changeover contact / 3PDT 10A/250 V	38

More about contact loadability on page 158.